

# BURDEN CARRIER BC-620<sup>NXG</sup>

## TOW LOAD- 5,000 LBS



PACK MULE



OUTPERFORMS  
OUTSMARTS  
OUTRUNS  
IT'S NXG



VEHICLE IS SHOWN WITH OPTIONAL EQUIPMENT



## STANDARD FEATURES ON OUR BC-620<sup>NXG</sup>

AC Drive System • Industry Leading 3-Year Warranty • Dual Front Wheels • Programmable Performance Characteristics (Maximum Speed, Acceleration Rate, Etc.) • Heavy Duty 245 Amp/Hour Batteries • Premium On-Board High Frequency Charger With Temperature Compensation & Automatic Cell Equalization To Extend The Life Of The Batteries • Sealed Direct Drive Transaxle • Heavy Duty Horn • Maintenance Management System Universal Hitch Plate • Dashboard Smart Gauge (LED Battery Status, Hour Meter & Diagnostic Codes) • State-Of-The Art, Fully Sealed, Tamper Proof & Programmable Controller With On-Board Diagnostics • Programmable Regenerative Braking • Extra Heavy-Duty Steel Construction(10 Gauge Uni-Body Internal Frame & 14 Gauge Genuine Diamond Plate Exterior) • Hall Affect Throttle Control • Contactor-Less Drive System • 6 Ply Load Range C Tires • Steering Wheel • Coil Spring Suspension • Bench Seat • Parking Brake



# BURDEN CARRIER BC-620<sup>NXG</sup>



**STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS**

## OPTIONAL EQUIPMENT

- Upgrade to Maintenance Free AGM 260 Amp/Hour Batteries
- Roll Out Battery Exchange System
- Carts with Chargers for Roll Out Batteries
- Solid Rubber Tires
- Solid Non-Marking Rubber Tires
- Cushion Solid Rubber Tires
- Left Foot Operator's Presence Switch
- Back-Up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Head Light, Tail Light, Brake Light
- Hand Lever Parking Brake
- Automotive Steering System
- Handle Bar Steering
- Galvanized & Stainless Steel Decks
- Galvanized Frame
- Protective Front Guard with Rubber Bumpers
- Stake Bed
- Custom Cargo Restraints
- Mounted Clipboards (Large and Small)
- Variety of Hitches
- Perma-Key Switch
- Programmable Key Switch
- 12 Volt Power Supply for Electronic Devices
- Diagnostic Handset
- 6,000 Towing Capacity
- Custom Colors
- High Capacity On-Board Charger, Reduces Charge Time by up to 30% (48-Volt Only)

## DIMENSIONS

- LENGTH: 105" (266.7 CM)
- WIDTH: 36" (91.4 CM)
- HEIGHT: 44" (111.8 CM)
- WHEEL BASE: 71" (180.3 CM)
- GROUND CLEARANCE: 3" (7.6 CM)
- DECK HEIGHT: 22.5" (57.2 CM)
- DECK: REAR: 35.5" (90 CM) X 48.0" (121.9 CM)  
FRONT: 35.5" (90.2 CM) X 18" (45.7 CM)
- TURNING RADIUS: 92" (233.7 CM)

## CAPACITIES

- MAXIMUM PERSONNEL: 2
- DECK: 1,000 LBS. (453.6 KG)
- TOWING: 2,000 LBS. (907.2KG)

## WHEELS & TIRES

- WHEELS: 4
- TIRES: PNEUMATIC 4.80 X 8 LRC (6 PLY)

## ELECTRICAL

- BATTERIES: 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY): 24 V (4 - 6V), 36 V (6 - 6 V), 48 V (6 - 8 V)
- SEALED MOTOR: 9.7 HP (24 V), 13.2 HP (36 V), 17.7 HP (48 V)
- SEALED PROGRAMMABLE CONTROLLER: 300 AMP (24 V), 330 AMP (36 V AND 48 V)
- ON-BOARD HIGH FREQUENCY CHARGER: 25 AMP (24 V), 21 AMP (36V), 18 AMP (48 V)
- KEY SWITCH: REMOVABLE SAFETY KEY SWITCH
- HORN: PUSH BUTTON ON CONSOLE

## STEERING, BRAKES & TRANSAXLE

- STEERING: 3-Spoke Steering wheel
- SERVICE BRAKES: Self- Adjusting Wheel Drum Brakes
- ELECTRONIC BRAKES: Programmable Electronic Regenerative Braking
- PARKING BRAKE: Foot- Operated Parking Brake
- TRANSAXLE: Sealed Heavy-Duty Direct Drive Helical Gear with 12.44:1 Ratio
- SUSPENSION: Coil Spring Rear

**AMERICAN BUILT**



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



**Call 800-241-2869**

**www.packmule.com**  
**www.wesleyinternational.com**