

# BURDEN CARRIER BCG-6200<sup>NXG</sup>

## TOW LOAD- 8,000 LBS



PACK MULE



OUTPERFORMS  
OUTSMARTS  
OUTRUNS  
IT'S NXG



VEHICLE IS SHOWN WITH OPTIONAL EQUIPMENT



## STANDARD FEATURES ON OUR BCG-6200<sup>NXG</sup>

AC Drive System • Industry Leading 3-Year Warranty • Dual Front Wheels • Programmable Performance Characteristics (Maximum Speed, Acceleration Rate, Etc.) • Heavy Duty 245 Amp/Hour Batteries • Premium On-Board High Frequency Charger With Temperature Compensation & Automatic Cell Equalization To Extend The Life Of The Batteries • Sealed Direct Drive Transaxle • Heavy Duty Horn • Maintenance Management System Universal Hitch Plate • Dashboard Smart View Display (LED Battery Status, Hour Meter & Diagnostic Codes) • State-Of-The Art, Fully Sealed, Tamper Proof & Programmable Controller With On-Board Diagnostics • Programmable Regenerative Braking • Extra Heavy-Duty Steel Construction(10 Gauge Uni-Body Internal Frame & 14 Gauge Genuine Diamond Plate Exterior) • Hall Affect Throttle Control • Contactor-Less Drive System • Solid Tires • Steering Wheel • Coil Spring Suspension • Bench Seat • Parking Brake • Left-foot Presence Switch

# BURDEN CARRIER BCG-6200<sup>NXG</sup>



**STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS**

## OPTIONAL EQUIPMENT

- Upgrade to Maintenance Free AGM 260 Amp/Hour Batteries
- Roll Out Battery Exchange System
- Carts with Chargers for Roll Out Batteries
- Solid Rubber Tires
- Solid Non-Marking Rubber Tires
- Cushion Solid Rubber Tires
- Back-Up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Head Light, Tail Light, Brake Light
- Hand Lever Parking Brake
- Automotive Steering System
- Handle Bar Steering
- Galvanized & Stainless Steel Decks
- Galvanized Frame
- Protective Front Guard with Rubber Bumpers
- Stake Bed
- Custom Cargo Restraints
- Mounted Clipboards (Large and Small)
- Variety of Hitches
- Perma-Key Switch
- Programmable Key Switch
- 12 Volt Power Supply for Electronic Devices
- Diagnostic HaNdsset
- 6,000 Towing Capacity
- Custom Colors
- High Capacity On-Board Charger, Reduces Charge Time by up to 30% (48-Volt Only)

## DIMENSIONS

- LENGTH: 85" (215.9 CM)
- WIDTH: 36" (91.4 CM)
- HEIGHT: 44" (111.8 CM)
- WHEEL BASE: 60.7" (154.2 CM)
- GROUND CLEARANCE: 3" (7.6 CM)
- DECK HEIGHT: 25.5" (64.8 CM)
- DECK: REAR: 35.5" (90 CM) X 25.0" (63.5 CM)  
FRONT: 35.5" (90.2 CM) X 21.3" (54.1 CM)
- TURNING RADIUS: 80" (203.2 CM)

## CAPACITIES

- MAXIMUM PERSONNEL: 2
- DECK: 1,200 LBS. (544.3 KG)
- TOWING: 8,000 LBS. (3628.7 KG)

## WHEELS & TIRES

- WHEELS: 4
- TIRES: SOLID 4.80 X 8

## ELECTRICAL

- BATTERIES: 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY): 48 V (6 - 8 V)
- SEALED MOTOR: 17.7 HP (48 V)
- SEALED PROGRAMMABLE CONTROLLER: 330 AMP (48 V)
- ON-BOARD HIGH FREQUENCY CHARGER: 18 AMP (48 V)
- KEY SWITCH: REMOVABLE SAFETY KEY SWITCH
- HORN: PUSH BUTTON ON CONSOLE

## STEERING, BRAKES & TRANSAXLE

- STEERING: 3-Spoke Steering wheel
- SERVICE BRAKES: Self-Adjusting Wheel Drum Brakes
- ELECTRONIC BRAKES: Programmable Electronic Regenerative Braking
- PARKING BRAKE: Foot- Operated Parking Brake
- TRANSAXLE: Sealed Heavy-Duty Direct Drive Helical Gear with 24:1 Ratio
- SUSPENSION: Leaf Spring Rear

**AMERICAN  
BUILT**



SPECIFICATIONS ARE SUBJECT  
TO CHANGE WITHOUT NOTICE



**Call 800-241-2869**

**www.packmule.com**  
**www.wesleyinternational.com**