



PACK MULE

RELIABLE PRODUCTS AND SERVICE



BURDEN CARRIER

HEAVY TOW - 5,000 LBS.



Warranty
Unlimited Hours
3 Years



BCT-5200 STANDARD FEATURES

- Industry Leading 3 Year Warranty
- Dual Front Wheels
- Programmable Performance Characteristics (Maximum Speed, Acceleration Rate, etc.)
- Heavy Duty 245 Amp/Hour Batteries
- Premium On-Board High Frequency Charger with temperature compensation & automatic cell equalization to extend the life of the batteries
- Precision Track, Direct Gear Steering
- Sealed Direct Drive Transaxle
- Heavy Duty Horn
- 6 Ply Load Range C Tires
- Maintenance Management System
- Dashboard Smart Gauge (L.E.D. Battery Status, Hour Meter & Diagnostic Codes)
- State-of-the Art, Fully Sealed, Tamper Proof & Programmable Controller with On-Board Diagnostics
- Programmable Regenerative Braking
- Extra Heavy-Duty Steel Construction (14 Gauge Genuine Diamond Plate Exterior)
- Electronic Throttle
- Contactor-less Drive System
- Universal Hitch Plate

BCT-5200

STOCK CHASER - BURDEN CARRIER - TOW TRACTOR - MAINTENANCE VEHICLE - PERSONNEL CARRIER

OPTIONAL EQUIPMENT
Upgrade to Maintenance Free AGM 250 Amp/Hour Batteries
AC Drive System
Roll Out Battery Exchange System
Carts with Chargers for Roll Out Batteries
Solid Rubber Tires
Solid Non-Marking Rubber Tires
Cushion Solid Rubber Tires
Left Foot Operator's Presence Switch
Back-Up Alarm
Proximity Alarm
Flashing Safety Beacon
Head Light, Tail Light, Brake Light
Hand Lever Parking Brake
Galvanized & Stainless Steel Decks
Galvanized Frame
Protective Front Guard with Rubber Bumpers
Extended Deck Lengths
Deck Shelves
Stake Bed
Custom Cargo Restraints
Modular Work Station
Mounted Clipboards (Large & Small)
Variety of Hitches
Perma-Key Switch
Programmable Key Switch
12 Volt Power Supply for Electronic Devices
Diagnostic Handset
6,000 Towing Capacity

DIMENSIONS	
Length	78 in. (198.1 cm)
Width	36 in. (91.4 cm)
Height	44 in. (111.8 cm)
Wheel Base	67 in (170.2 cm)
Ground Clearance	3 in. (7.6 cm)
Deck Height	22.5 in. (57.2 cm)
Deck	Rear: 35.5 in. (90.2 cm) x 30 in. (76.2 cm) / Front: 35.5 in. (90.2 cm) x 18 in. (45.7 cm)
Turning Radius	74.5 in. (189.2 cm)
CAPACITIES	
Maximum Personnel	2
Deck	1200 lbs. (544.3 kg)
Towing	5000 lbs. (2268 kg)
WHEELS & TIRES	
Wheels	4
Tires	Pneumatic 4.80 x 8 LRC (6 Ply)
ELECTRICAL	
Batteries	245 Amp-Hr Lead Acid, Commercial
System Voltage (Battery Quantity)	36 V. (6-6 V), 48 V. (8-6 V)
Sealed Motor (Separately Excited)	7.5 hp (36 V.), 10 hp (48 V.)
Sealed Programmable Controller	300 Amp (36 V.), 400 Amp (48 V.)
On-Board High Frequency Charger	21 Amp (36 V.), 18 Amp (48 V.)
Key Switch	Removable Safety Key Switch
Horn	Push Button on Console
STEERING, BRAKES, TRANSAXLE & SUSPENSION	
Steering	3-Spoke Contour Wheel
Service Brakes	Self- Adjusting Wheel Drum Brakes
Electronic Brakes	Programmable Electronic Regenerative Braking
Parking Brake	Foot-Operated Parking Brake
Heavy Duty Sealed Transaxle	Heavy-Duty Direct Drive Helical Gear with 16.99:1 Ratio