

PERSONNEL CARRIER PC-325

TOW LOAD- 2,000 LBS



PACK MULE



AC
STANDARD

OUTPERFORMS
OUTSMARTS
OUTRUNS
IT'S NXG



STANDARD FEATURES ON OUR PC-325^{NXG}

VEHICLE MIGHT BE SHOWN WITH OPTIONAL EQUIPMENT

AC DRIVE SYSTEM • INDUSTRY LEADING 3 YEAR WARRANTY • DUAL FRONT WHEELS • ONE PASSENGER • PROGRAMMABLE PERFORMANCE CHARACTERISTICS (MAXIMUM SPEED, ACCELERATION RATE, ETC.) • HEAVY DUTY 245 AMP/HOUR BATTERIES • PREMIUM ON-BOARD HIGH FREQUENCY CHARGER WITH TEMPERATURE COMPENSATION & AUTOMATIC CELL EQUALIZATION TO EXTEND THE LIFE OF THE BATTERIES • SEALED DIRECT DRIVE TRANSAXLE • HEAVY DUTY HORN • UNIVERSAL HITCH PLATE • LEFT FOOT OPERATOR'S PRESENCE SWITCH • DASHBOARD SMART GAUGE (L.E.D. BATTERY STATUS, HOUR METER & DIAGNOSTIC CODES) • STATE-OF-THE-ART, FULLY SEALED, TAMPER PROOF & PROGRAMMABLE CONTROLLER WITH ON-BOARD DIAGNOSTICS • PROGRAMMABLE REGENERATIVE BRAKING EXTRA HEAVY-DUTY STEEL CONSTRUCTION (10 GAUGE UNI-BODY INTERNAL FRAME & 14 GAUGE GENUINE DIAMOND PLATE EXTERIOR) • HALL EFFECT ELECTRONIC THROTTLE • CONTACTORLESS • DRIVE SYSTEM 6 PLY LOAD RANGE C TIRES • 2 WHEEL MECHANICAL DRUM BRAKING • COIL SPRING SUSPENSION

PERSONNEL CARRIER PC-325^{NXG}



STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS

OPTIONAL EQUIPMENT

- UPGRADE TO MAINTENANCE FREE AGM 250 AMP/HOUR BATTERIES
- ROLL OUT BATTERY EXCHANGE SYSTEM
- CARTS WITH CHARGERS FOR ROLL OUT BATTERIES
- SOLID SOFT TIRES
- SOLID NON-MARKING SOFT TIRES
- BACK-UP ALARM
- PROXIMITY ALARM
- FLASHING SAFETY BEACON
- HEAD LIGHT & TAIL LIGHT
- HAND LEVER PARKING BRAKE
- GALVANIZED & STAINLESS STEEL DECKS
- GALVANIZED FRAME
- PROTECTIVE FRONT GUARD WITH RUBBER BUMPERS
- STAKE BED
- CUSTOM CARGO RESTRAINTS
- MOUNTED CLIPBOARDS (LARGE AND SMALL)
- VARIETY OF HITCHES
- PERMA-KEY SWITCH
- PROGRAMMABLE KEY SWITCH
- 12 VOLT POWER SUPPLY FOR ELECTRONIC DEVICES
- DIAGNOSTIC HANDSET
- 5,000 TOWING CAPACITY
- AUTOMATIC ELECTRIC PARKING BRAKE
- AUTOMOTIVE STEERING SYSTEM
- BLUE SAFETY LIGHT

DIMENSIONS

- LENGTH: 74.5" (189.2 CM)
- WIDTH: 32" (81.3 CM)
- HEIGHT: 39" (99.1 CM)
- WHEEL BASE: 53.5" (135.9 CM)
- GROUND CLEARANCE: 3" (7.6 CM)
- DECK HEIGHT: 24" (61 CM)
- DECK: REAR: 31.5" (80 CM) X 19.5" (49.6 CM)
- TURNING RADIUS: 63.5" (161.3 CM)

CAPACITIES

- MAXIMUM PERSONNEL: 1
- DECK: 750LBS. (340.2 KG)
- TOWING: 2,000 LBS. (907.2 KG)

WHEELS & TIRES

- WHEELS: 4
- TIRES: PNEUMATIC 4.80 X 8 LRC (6 PLY)

ELECTRICAL

- BATTERIES: 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY): 24 V (4 - 6V), 36 V (6 - 6 V), 48 V (6 - 8 V)
- SEALED AC MOTOR: 9.7 HP (24 V), 13.2 HP (36 V), 17.7 HP (48 V)
- SEALED PROGRAMMABLE CONTROLLER: 300 AMP (24 V), 330 AMP (36 V AND 48 V)
- ON-BOARD HIGH FREQUENCY CHARGER: 25 AMP (24 V), 21 AMP (36 V), 18 AMP (48 V)
- KEY SWITCH: REMOVABLE SAFETY KEY SWITCH
- HORN: HD

STEERING, BRAKES & TRANSAXLE

- STEERING: TILLER
- SERVICE BRAKES: MECHANICAL SELF-ADJUSTING DRUM BRAKES
- ELECTRONIC BRAKES: PROGRAMMABLE ELECTRONIC REGENERATIVE BRAKING
- PARKING BRAKE: FOOT-OPERATED PARKING BRAKE
- HEAVY DUTY SEALED TRANSAXLE: HEAVY-DUTY DIRECT DRIVE HELICAL GEAR WITH 12.44:1 RATIO
- SUSPENSION: COIL SPRING REAR

AMERICAN
BUILT



Call 800-241-2869

www.packmule.com
www.wesleyinternational.com