

PERSONNEL CARRIER PC-640^{NXG}

TOW LOAD- 2,000 LBS



PACK MULE



OUTPERFORMS
OUTSMARTS
OUTRUNS
IT'S NXG



STANDARD FEATURES ON OUR PC-640^{NXG}

VEHICLE MIGHT BE SHOWN WITH OPTIONAL EQUIPMENT

AC DRIVE SYSTEM • INDUSTRY LEADING 3 YEAR WARRANTY • 4 PASSENGER • PROGRAMMABLE PERFORMANCE CHARACTERISTICS (MAXIMUM SPEED, ACCELERATION RATE, ETC.) • HEAVY DUTY 245 AMP/HOUR BATTERIES • PREMIUM ON-BOARD HIGH FREQUENCY CHARGER WITH TEMPERATURE COMPENSATION & AUTOMATIC CELL EQUALIZATION TO EXTEND THE LIFE OF THE BATTERIES • SEALED DIRECT DRIVE TRANSAXLE • HEAVY DUTY HORN • UNIVERSAL HITCH PLATE • DASHBOARD SMART GAUGE (L.E.D. BATTERY STATUS, HOUR METER & DIAGNOSTIC CODES) • STATE-OF-THE-ART, FULLY SEALED, TAMPER PROOF & PROGRAMMABLE CONTROLLER WITH ON-BOARD DIAGNOSTICS • PROGRAMMABLE REGENERATIVE BRAKING • EXTRA HEAVY-DUTY STEEL CONSTRUCTION (10 GAUGE UNI-BODY INTERNAL FRAME & 14 GAUGE GENUINE DIAMOND PLATE EXTERIOR) • HALL EFFECT ELECTRONIC THROTTLE • CONTACTOR-LESS DRIVE SYSTEM • 6 PLY LOAD RANGE C TIRES • CONTOUR STEERING WHEEL

PERSONNEL CARRIER PC-640^{NXG}



STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS

OPTIONAL EQUIPMENT

- UPGRADE TO MAINTENANCE FREE AGM 260 AMP/HOUR BATTERIES
- ROLL OUT BATTERY EXCHANGE SYSTEM
- CARTS WITH CHARGERS FOR ROLL OUT BATTERIES
- SOLID NON-MARKING SOFT TIRES
- CUSHION SOLID SOFT TIRES
- BACK-UP ALARM
- PROXIMITY ALARM
- FLASHING SAFETY BEACON
- HEAD LIGHT, TAIL LIGHT, BRAKE LIGHT
- HAND LEVER PARKING BRAKE
- AUTOMOTIVE STEERING SYSTEM
- HANDLE BAR STEERING
- GALVANIZED & STAINLESS STEEL DECKS
- GALVANIZED FRAME
- PROTECTIVE FRONT GUARD WITH RUBBER BUMPERS
- STAKE BED
- CUSTOM CARGO RESTRAINTS
- MOUNTED CLIPBOARDS (LARGE AND SMALL)
- VARIETY OF HITCHES
- PERMA-KEY SWITCH
- PROGRAMMABLE KEY SWITCH
- 12 VOLT POWER SUPPLY FOR ELECTRONIC DEVICES
- DIAGNOSTIC HEADSET
- 6,000 TOWING CAPACITY
- CUSTOM COLORS
- HIGH CAPACITY ON-BOARD CHARGER, REDUCES CHARGE TIME BY UP TO 30% (48 VOLT ONLY)
- MAINTENANCE MANAGEMENT SYSTEM
- AUTOMATIC ELECTRIC PARKING BRAKE

DIMENSIONS

- LENGTH- 104" (264.2 CM)
- WIDTH – 36" (91.4 CM)
- HEIGHT – 44" (111.8 CM)
- WHEEL BASE- 80" (203.2 CM)
- GROUND CLEARANCE – 3" (7.6 CM)
- DECK HEIGHT – 24" (61 CM)
- DECK – REAR: 35.5" (90.2 CM) X 14" (35.6 CM)
FRONT: 35.5 (90.2 CM) X 18" (45.7 CM)
- TURNING RADIUS – 92" (233.7 CM)

CAPACITIES

- MAXIMUM PERSONNEL – 4
- DECK – 1,000LBS. (453.6.2 KG)
- TOWING – 2,000 LBS. (907.2 KG)

WHEELS & TIRES

- WHEELS – 4
- TIRES – PNEUMATIC 4.80 X 8 LRC (6 PLY)

ELECTRICAL

- BATTERIES – 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY) – 24 V (4 - 6V), 36 V (6 - 6 V), 48 V (8 - 6 V)
- SEALED AC MOTOR – 9.7 HP (24V), 13.2 HP (36V), 17.7 HP (48V)
- SEALED PROGRAMMABLE CONTROLLER – 300 AMP (24V), 330 AMP (36V & 48V)
- ON-BOARD HIGH FREQUENCY CHARGER – 25 AMP (24 V), 18 AMP (48 V)
- KEY SWITCH- REMOVABLE SAFETY KEY SWITCH
- HORN – HD

STEERING, BRAKES & TRANSAXLE

- STEERING – CONTOUR STEERING WHEEL
- SERVICE BRAKES – MECHANICAL SELF-ADJUSTING DRUM BRAKES
- ELECTRONIC BRAKES – PROGRAMMABLE ELECTRONIC REGENERATIVE BRAKING
- PARKING BRAKE – FOOT- OPERATED PARKING BRAKE
- HEAVY DUTY SEALED TRANSAXLE – HEAVY-DUTY DIRECT DRIVE HELICAL GEAR WITH 12.44:1 RATIO

AMERICAN
BUILT



Call 800-241-2869

www.packmule.com
www.wesleyinternational.com