

STOCK CHASER SC-775^{NXG}

TOW LOAD - 2,000LBS



PACK MULE



OUTPERFORMS
OUTSMARTS
OUTRUNS
IT'S NXG



STANDARD FEATURES ON OUR SC-775^{NXG}

VEHICLE IS SHOWN WITH OPTIONAL EQUIPMENT

AC DRIVE SYSTEM • INDUSTRY LEADING 3 YEAR WARRANTY • DUAL FRONT WHEELS • PROGRAMMABLE PERFORMANCE CHARACTERISTICS (MAXIMUM SPEED, ACCELERATION RATE, ETC) HEAVY DUTY 245 AMP/HOUR BATTERIES • PREMIUM ON-BOARD PROGRAMMABLE HIGH FREQUENCY CHARGER WITH TEMPERATURE COMPENSATION & AUTOMATIC CELL EQUALIZATION TO EXTEND THE LIFE OF THE BATTERIES • PRECISION TRACK, RACK & PINION STEERING • SEALED DIRECT DRIVE TRANSAXLE • HEAVY DUTY HORN • 6 PLY LOAD RANGE C TIRES • KEY SWITCH MAINTENANCE MANAGEMENT SYSTEM • DASHBOARD SMART GAUGE BATTERY STATUS, HOUR METER DIAGNOSTIC CODES • STATE-OF-THE-ART, FULLY SEALED, TAMPER PROOF & PROGRAMMABLE CONTROLLER WITH ON-BOARD DIAGNOSTICS • DUAL STAGE REGENERATIVE BRAKING EXTRA HEAVY-DUTY UNI-BODY STEEL CONSTRUCTION (10 GAUGE INTERNAL FRAME & 14 GAUGE GENUINE DIAMOND PLATE EXTERIOR) • HALL-EFFECT ELECTRONIC THROTTLE CONTROL • CONTACTOR-LESS DRIVE SYSTEM • UNIVERSAL HITCH PLATE ERGONOMIC COMFORT MATTING • ADJUSTABLE BACKREST • CONTOUR STEERING WHEEL • SPARE 250 AMP FUSE

STOCK CHASER SC-775^{NXG}



STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS

OPTIONAL EQUIPMENT

- UPGRADE TO MAINTENANCE FREE AGM 260 AMP/HOUR BATTERIES
- ROLL OUT BATTERY EXCHANGE SYSTEM
- ROLL OUT BATTERY CART WITH CHARGER
- INDUSTRIAL BATTERY & CHARGER
- SOLID SOFT TIRES
- SOLID NON-MARKING SOFT TIRES
- BACK-UP ALARM
- VEHICLE IN MOTION ALARM
- FLASHING SAFETY BEACON
- HEAD LIGHT/ TAIL LIGHT, REVERSE & BRAKE LIGHT
- HAND LEVER PARKING BRAKE
- GALVANIZED & STAINLESS STEEL DECKS
- GALVANIZED FRAME
- PROTECTIVE FRONT GUARD WITH RUBBER BUMPERS
- EXTENDED DECK LENGTHS
- 5 OR 6 STEP LADDER (87" OR 95")
- DECK SHELVES
- STAKE BED/RAILS
- CUSTOM CARGO RESTRAINTS
- MODULAR WORK STATION
- MOUNTED CLIPBOARDS (LARGE AND SMALL)
- VARIETY OF HITCHES
- PERMA-KEY SWITCH
- PROGRAMMABLE KEY SWITCH
- 12 VOLT POWER SUPPLY FOR ELECTRONIC DEVICES
- DIAGNOSTIC HANDSET
- 5,000 TOWING CAPACITY
- ELECTRIC PARKING BRAKE
- SINGLE POINT BATTERY WATERING SYSTEM
- BLUE SAFETY LIGHT
- USB POWER PLUG
- EXTENDED LENGTH CHARGE CORD
- EXTERNAL CHARGERS
- MAINTENANCE MANAGEMENT SYSTEM

DIMENSIONS

- LENGTH: 78" (198.1 CM)
- WIDTH: 32" (81.3 CM)
- HEIGHT: 50" (127CM)
- WHEEL BASE: 40" (101.6 CM)
- GROUND CLEARANCE: 3" (7.6 CM)
- DECK HEIGHT: 24" (61 CM)
- DECK: FRONT: 31.5" (80 CM) X 48" (121.9 CM)
- TURNING RADIUS: 55" (139.7 CM)

CAPACITIES

- MAXIMUM PERSONNEL: 1
- DECK: 1,000 LBS. (453.6 KG)
- TOWING: 2,000 LBS. (907.2 KG)

WHEELS & TIRES

- WHEELS: 4
- TIRES: PNEUMATIC 4.80 X 8 LRC (6 PLY)

ELECTRICAL

- BATTERIES: 245 AMP-HR LEAD ACID, COMMERCIAL
- SYSTEM VOLTAGE (BATTERY QUANTITY): 24 V (4 - 6 V), 36 V (6 - 6 V), 48 V (6 - 8 V)
- SEALED AC MOTOR: 9.6 HP (24 V), 13.2 HP (36 V), 17.7 HP (48 V)
- SEALED PROGRAMMABLE CONTROLLER: 330 AMP (36 V & 48 V), 360 AMP (24 V)
- ON-BOARD HIGH FREQUENCY CHARGER: 25 AMP (24 V), 21 AMP (36 V), 18 AMP (48 V)
- KEY SWITCH: REMOVABLE SAFETY KEY SWITCH
- HORN: PUSH BUTTON ON CONSOLE
- LEFT FOOT OPERATOR'S PRESENCE SWITCH

STEERING, BRAKES & TRANSAXLE

- STEERING: 3-SPOKE CONTOUR WHEEL
- SERVICE BRAKES: MECHANICAL SELF-ADJUSTING WHEEL DRUM BRAKES
- ELECTRONIC BRAKES: PROGRAMMABLE ELECTRONIC REGENERATIVE BRAKING
- PARKING BRAKE: AUTOMATIC PARKING BRAKE
- HEAVY DUTY SEALED TRANSAXLE: HEAVY-DUTY DIRECT DRIVE HELICAL GEAR WITH 12.44:1 RATIO

AMERICAN
BUILT



SPECIFICATIONS ARE SUBJECT
TO CHANGE WITHOUT NOTICE



Call 800-241-2869

www.packmule.com
www.wesleyinternational.com