

STOCK CHASER SCT-7750IB^{NXG}

HEAVY TOW - 5,000 LBS / 36-VOLT



PACK MULE



OUTPERFORMS
OUTSMARTS
OUTRUNS
IT'S NXG



STANDARD FEATURES ON OUR SCT-7750^{NXG}

VEHICLE IS SHOWN WITH OPTIONAL EQUIPMENT

AC DRIVE SYSTEM • INDUSTRY LEADING 3 YEAR WARRANTY • DUAL FRONT WHEELS • PROGRAMMABLE PERFORMANCE CHARACTERISTICS (MAXIMUM SPEED, ACCELERATION RATE, ETC) • 36 VOLT, 330 AMP/HR, INDUSTRIAL BATTERY • PRECISION TRACK, DIRECT GEAR STEERING • HD SEALED DIRECT DRIVE TRANSAXLE WITH FORGED FLANGED AXLES • HEAVY DUTY HORN • 6 PLY LOAD RANGE C TIRES • HAND LEVER PARKING BRAKE • DASHBOARD SMART GAUGE (LED BATTERY STATUS, HOUR METER & DIAGNOSTIC CODES) • STATE OF THE ART, FULLY SEALED, TAMPER PROOF & PROGRAMMABLE CONTROLLER WITH ON-BOARD DIAGNOSTICS • PROGRAMMABLE REGENERATIVE BRAKING • EXTRA HEAVY-DUTY STEEL CONSTRUCTION (10 GAUGE UNI-BODY INTERNAL FRAME & 14 GAUGE GENUINE DIAMOND PLATE EXTERIOR) • HALL EFFECT THROTTLE CONTROL • CONTACTORLESS DRIVE SYSTEM • UNIVERSAL HITCH PLATE • ERGONOMIC COMFORT MATTING • CONTOUR STEERING WHEEL • ADJUSTABLE BACKREST • SPARE 250 AMP FUSE

STOCK CHASER SCT-7750^{NXG}



STOCK CHASERS • BURDEN CARRIERS • TOW TRACTORS • MAINTENANCE VEHICLES • PERSONNEL CARRIERS

OPTIONAL EQUIPMENT

- 36 V 330 AH INDUSTRIAL BATTERY
- TWO TYPES OF CHARGERS: HIGH FREQUENCY OPPORTUNITY CHARGE CAPABLE CHARGER AND STANDARD, FERRO RESONANT TRANSFORMER CHARGER
- SOLID SOFT TIRES
- SOLID NON- MARKING SOFT TIRES
- BACK-UP ALARM
- PROXIMITY ALARM
- FLASHING SAFETY BEACON
- HEAD LIGHT, TAIL LIGHT
- HAND LEVER PARKING BRAKE
- GALVANIZED & STAINLESS STEEL DECKS
- GALVANIZED FRAME
- PROTECTIVE FRONT GUARD WITH RUBBER BUMPERS
- EXTENDED DECK LENGTHS
- 5 OR 6 STEP LADDER (87 IN OR 95 IN)
- DECK SHELVES
- STAKE BED/RAILS
- CUSTOM CARGO RESTRAINTS
- MODULAR WORK STATION
- MOUNTED CLIPBOARDS (LARGE AND SMALL)
- VARIETY OF HUTCHES
- PERMA-KEY SWITCH
- PROGRAMMABLE KEY SWITCH
- 12 VOLT POWER SUPPLY FOR ELECTRONIC DEVICES
- DIAGNOSTIC HANDSET
- 6,000 TOWING CAPACITY
- AUTOMATIC ELECTRIC PARKING BRAKE
- BLUE SAFETY LIGHT
- MAINTENANCE MANAGEMENT SYSTEM
- 36 VOLT INDUSTRIAL BATTERY CHARGER
- 24 VOLT INDUSTRIAL BATTERY
- 24 VOLT INDUSTRIAL BATTERY CHARGER

DIMENSIONS

- LENGTH: 78" (198.1 CM)
- WIDTH: 32" (81.3 CM)
- HEIGHT: 50" (127CM)
- WHEEL BASE: 40" (101.6 CM)
- GROUND CLEARANCE: 3" (7.6 CM)
- DECK HEIGHT: 24" (61 CM)
- DECK: FRONT: 31.5" (80 CM) X 48" (121.9 CM)
- TURNING RADIUS: 55" (139.7 CM)

CAPACITIES

- MAXIMUM PERSONNEL: 1
- DECK: 1,200LBS. (544.3 KG)
- TOWING: 5,000 LBS. (2,268 KG)

WHEELS & TIRES

- WHEELS: 4
- TIRES: PNEUMATIC 4.80 X 8 LRC (6 PLY)

ELECTRICAL

- BATTERIES COMPARTMENT- BATTERY COMPARTMENT IS 31.85" L X 15.1" W X 14.6" H TO ACCOMMODATE OPTIONAL 24 V INDUSTRIAL BATTERY
- SYSTEM VOLTAGE: 36 V
- SEALED AC MOTOR: 13.2HP (36 V)
- SEALED PROGRAMMABLE CONTROLLER: 330 AMP (36 V)
- CHARGER: CHARGER OPTIONAL TO FIT BATTERY SELECTED & PREFERRED CHARGING METHOD
- KEY SWITCH: REMOVABLE SAFETY KEY SWITCH
- HORN: PUSH BUTTON ON CONSOLE
- LEFT FOOT OPERATOR'S PRESENCE SWITCH

STEERING, BRAKES & TRANSAXLE

- STEERING: 3-SPOKE CONTOUR WHEEL
- SERVICE BRAKES: SELF- ADJUSTING WHEEL DRUM BRAKES
- ELECTRONIC BRAKES: PROGRAMMABLE ELECTRONIC REGENERATIVE BRAKING
- PARKING BRAKE: AUTOMATIC PARKING BRAKE
- HEAVY DUTY SEALED TRANSAXLE: HEAVY-DUTY DIRECT DRIVE HELICAL GEAR WITH 16.99:1 RATIO

**AMERICAN
BUILT**



SPECIFICATIONS ARE SUBJECT
TO CHANGE WITHOUT NOTICE



Call 800-241-2869

www.packmule.com
www.wesleyinternational.com