



PACK MULE

RELIABLE PRODUCTS AND SERVICE



TOW VEHICLE

TOW LOAD - 5,000 LBS.



Warranty
Unlimited Hours
3 Years

PCT-3200 STANDARD FEATURES

- Industry Leading 3 Year Warranty
- Dual Front Wheels
- Programmable Performance Characteristics (Maximum Speed, Acceleration Rate, etc.)
- Heavy Duty 245 Amp/Hour Batteries
- Premium On-Board High Frequency Charger with temperature compensation & automatic cell equalization to extend the life of the batteries
- Sealed Direct Drive Transaxle
- Heavy Duty Horn
- Maintenance Management System
- Universal Hitch Plate
- Dashboard Smart Gauge (L.E.D. Battery Status, Hour Meter & Diagnostic Codes)
- State-of-the Art, Fully Sealed, Tamper Proof & Programmable Controller with On-Board Diagnostics
- Programmable Regenerative Braking
- Extra Heavy-Duty Steel Construction (10 Gauge Uni-Body Internal Frame & 14 Gauge Genuine Diamond Plate Exterior)
- Electronic Throttle
- Contactor-less Drive System
- 6 Ply Load Range C Tires

PCT-3200

TOW TRACTOR - PERSONNEL CARRIER - MAINTENANCE VEHICLE

OPTIONAL EQUIPMENT
Upgrade to Maintenance Free AGM 250 Amp/Hour Batteries
AC Drive System
Roll Out Battery Exchange System
Carts with Chargers for Roll Out Batteries
Solid Rubber Tires
Solid Non-Marking Rubber Tires
Cushion Solid Rubber Tires
Left Foot Operator's Presence Switch
Back-Up Alarm
Proximity Alarm
Flashing Safety Beacon
Head Light, Tail Light, Brake Light
Hand Lever Parking Brake
Ergonomic Bucket Seat
Galvanized & Stainless Steel Decks
Galvanized Frame
Protective Front Guard with Rubber Bumpers
Stake Bed
Custom Cargo Restraints
Mounted Clipboards (Large & Small)
Variety of Hitches
Perma-Key Switch
Programmable Key Switch
12 Volt Power Supply for Electronic Devices
Diagnostic Handset

DIMENSIONS	
Length	86.5 in. (219.7 cm)
Width	32 in. (81.3 cm)
Height	39 in. (99.1 cm)
Wheel Base	53.5 in (135.9 cm)
Ground Clearance	3 in. (7.6 cm)
Deck Height	24 in. (61 cm)
Deck	Rear: 31.5 in. (80 cm) x 19.5 (49.6 cm)
Turning Radius	63.5 in. (161.3 cm)
CAPACITIES	
Maximum Personnel	2
Deck	750 lbs. (340.2kg)
Towing	5000 lbs. (2268 kg)
WHEELS & TIRES	
Wheels	4
Tires	Pneumatic 4.80 x 8 LRC (6 Ply)
ELECTRICAL	
Batteries	245 Amp-Hr Lead Acid, Commercial
System Voltage (Battery Quantity)	36 V. (6-6 V), 48 v. (8-6 V.)
Sealed Motor (Separately Excited)	7.5 hp (36 V.), 10 hp (48 V.)
Sealed Programmable Controller	300 Amp (36 V.), 400 Amp (48 V.)
On-Board High Frequency Charger	21 Amp (36 V.), 18 Amp (48 V.)
Key Switch	Removable Safety Key Switch
Horn	Foot-Operated Push Button
STEERING, BRAKES, TRANSAXLE & SUSPENSION	
Steering	Tiller
Service Brakes	Self-Adjusting Wheel Drum Brakes
Electronic Brakes	Programmable Electronic Regenerative Braking
Parking Brake	Foot-Operated Parking Brake
Heavy Duty Sealed Transaxle	Heavy-Duty Direct Drive Helical Gear with 12.44:1 Ratio
Suspension	Coil Spring Rear