

WHY CHOOSE PACK MULE?

PACK MULE's NXG Personnel Carriers provide rapid transport in multiple configurations including cargo and towing capability. Whether you need to move multiple staff, supervisors or VIPs, Pack Mule's Personnel Carriers are designed for years of safe, comfortable and reliable operation in all environments. Skeptical? Ask us to prove it!

We've been helping manufacturers and distributors move materials horizontally for more than 60 years, and we've learned what customers need to get the job done. That's the reason we build PACK MULE to a higher standard—and that's why we encourage you to test them in your facility, doing your work.

Try a **PACK MULE** vehicle and/or trailer in your facility. No commitment required.

TO SCHEDULE A DEMO AT YOUR FACILITY EMAIL SALES@PACKMULE.COM OR CALL:

800-241-2869

PACK MULE

WWW.PACKMULE.COM SALES@PACKMULE.COM

PERFORMANCE

- · Brushless, Sealed, High-Performance AC Motor
- Heavy-Duty 245 Amp/Hr Batteries
- 120V Plug-In On-Board High-Frequency Charger
- Programmable Speed & Acceleration
- · Dual Stage Regenerative Braking

DURABILITY

- Heavy-Duty 14 ga. Genuine Diamond Plate Exterior.
- Dual Front Wheels w/ 90 PSI Low-rolling-friction tires
- Maintenance-Free Sealed AC Motor, Electronic Drive System, Wheel Bearings and Transaxle.

ERGONOMICS

- Smart-View Dashboard Display with Battery Status, Hour Meter & On-Board Diagnostics.
- · Coil Spring Suspension
- Handlebar Steering
- Universal Hitch Plate

SAFETY

- Programmable Performance & Safety Characteristics (Maximum speed, Acceleration Rate, Etc.)
- Self-Adjusting Service Brake & Manual Parking Brake
- Driver Presence Seat Sensor

DEPENDABILITY

- Unsurpassed 3 Year Unlimited-Hour Warranty
- · Dual Hall Effect Throttle Position Sensor
- · Contactorless Drive System



PACK MULE ELECTRIC UTILITY VEHICLES

PERSONNEL CARRIER / TUGGER PCT-3500 NXG







CAPACITY

DECK CAPACITY	TOW CAPACITY	PERSONNEL
750 LB	5000 LB	1

DIMENSIONS

CHASSIS	LENGTH	WIDTH	HEIGHT
	80" (203.2cm)	32" (81.3cm)	44" (111.8cm)
DECK	LENGTH	WIDTH	HEIGHT
	21.5" (54.6cm)	31.5" (80cm)	24" (61cm)

WHEEL BASE	GROUND CLEAR.	TURN RADIUS
53.5" (135.9cm)	3" (7.6cm)	76" (193cm)

ELECTRICAL

	36 VOLT	48 VOLT			
VOLTAGE (BATTERY QTY)					
	(6) 6V	(8) 6V			
ON-BOARD CHARGER (INPUT VOLTAGE 120V)					
	21 AMP	18 AMP			
HORSEPOWER (SEALED AC MOTOR)					
	13.2 HP	17.7 HP			
•					

TO SCHEDULE A DEMO AT YOUR FACILITY **EMAIL SALES@PACKMULE.COM OR CALL:** 800-241-2869





OPTIONS & UPGRADES

MAINTENANCE-FREE. WORRY-FREE UPGRADES

- Soft-Solid Tires (3 year warranty)
- Battery Watering System
- AGM 260 Amp/Hr Batteries

SAFETY & AWARENESS UPGRADES

- Reverse Beeper & Proximity Alarm
- LED Flashing Safety Beacon (Blue or Amber)
- Blue Safety Light
- · LED Head, Tail, Brake and Reverse Lights
- Protective Front Guard with Bumper
- Programmable Security Keypad
- · Automatic Electric Parking Brake
- · Programming & Diagnostic Handset
- · Safety Presence Foot Switch

CONVENIENCE UPGRADES

- · Permanent Key Switch
- Contour Steering Wheel
- Tiller Steering
- 12V Power Supply for Electronic Devices
- Roll-out Battery Charging & Exchange System
- · High Capacity On-Board Charger

CARGO UPGRADES

- Stake Bed & Cargo Restraints
- · Galvanized & Stainless Steel Decks
- · Tow Hooks & Hitches

OTHER UPGRADES

- Custom Colors
- · Solid Non-Marking Tires
- Galvanized Frame
- Industrial battery



TOW CAPACITY